



August 29, 2012

Sent via Certified Mail Number: | 7003 0500 005 0922 3253

Dan Weintraub, Director
Greenovative Technologies
A JSH International Company
303 Birchfield Drive
Mount Laurel, NJ 08054

Re: Review for Compliance with FS381.0065(4)(m) – **“TSS – Total System Solution”**

Dear Mr. Weintraub:

This letter is to acknowledge receipt of information regarding the proposed use of the product, **“TSS – Total System Solution”** for statewide use in Florida. No product sold in the state for use in onsite sewage treatment and disposal systems may contain any substance in concentrations or amounts that would interfere with or prevent the successful operation of such system, or that would cause discharges from such systems to violate applicable water quality standards, section 381.0065(4)(m), Florida Statutes (FS).

The department has reviewed the information provided in the MSDS, LC₅₀ value reported from the 96-Hr Acute Definitive Toxicity test, and laboratory analysis of VOCs for the **“TSS – Total System Solution”** product. Based on this information, the department has determined that the proposed formulation and use of the product, **“TSS – Total System Solution”** complies with s. 381.0065(4)(m), FS, and the criteria published in rule 64E-6.0151, Florida Administrative Code (FAC). The reviewed formulation, application instructions, and description are for compliant application rates of:

- 16 oz for internal grease traps of 50 gallons or less with at least 500 gallons of additional system liquid capacity.
- 32 oz for internal grease traps of 51-75 gallons with at least 1,000 gallons of additional system liquid capacity.
- 48 oz for internal grease traps of 76-150 gallons with at least 1,400 gallons of additional system liquid capacity.
- 44 oz when the combined grease trap and septic tank liquid capacity is less than 2,500 gallons, but greater than 1,248 gallons.
- 88 oz when the combined grease trap and septic tank liquid capacity is 2,500 gallons or more.
- Composed of ingredients as listed in the reviewed documents.

The department has no objection to the use of the product under this name, and in accordance with the manufacturer's instructions as reviewed. Please be advised that all rules pertaining to the use of the product shall be observed and that there shall be no advertising of the product as state approved.

Bureau of Environmental Health

4052 Bald Cypress Way, Bin A08 • Tallahassee, Florida 32399-1713
Phone: (850) 245-4070 • Fax: (850) 922-6969 • <http://www.MyFloridaEH.com>

Mr. Dan Weintraub
Page #2
August 29, 2012

Be advised that the department is not a testing agency and that this determination reflects only a review of the information submitted by you for compliance with Florida Statutes and Florida Administrative Code. The product evaluation does not investigate the validity of performance claims by manufacturers. For this reason, departmental determination of compliance must not be interpreted as certifying effectiveness, endorsing, or recommending use of an additive. The Florida Department of Health also does not assume liability for any promise, guarantee, or expectation from purchasing or using an additive. The department reserves the right to withdraw acceptance if product formulation, ingredients, or labeling are modified after product evaluation by the department or subsequently found not to comply with rule 64E-6.0151, FAC, or chapter 381.0065, F.S.

This letter of product compliance for the product "**TSS – Total System Solution**" is limited to Department of Health jurisdictional circumstances as defined in Chapter 64E-6, Florida Administrative Code and Chapter 381.0065, Florida Statutes.

If we may be of further assistance or should you have any additional questions regarding this letter, please contact Marcelo J. Blanco by email at Marcelo_Blanco@doh.state.fl.us or by phone at (407) 316-4540.

Sincerely,


Gerald Briggs, Environmental Administrator
Water and Onsite Sewage Section

GB/mjb

NOTICE OF RIGHTS TO APPEAL

A party whose substantial interest is affected by this order may petition for an administrative hearing pursuant to Sections 120.569 and 120.57, Florida Statutes. Such proceedings are governed by Chapter 28-106, Florida Administrative Code. A petition for a hearing must be in writing and must be received by the Agency Clerk for the Department within twenty-one (21) days from the receipt of this order. The address for the Agency Clerk is 4052 Bald Cypress Way, Bin # A02, Tallahassee, FL 32399-1703. The Agency Clerk's facsimile number is (850) 410-1448.

Mediation is not available as an alternative remedy.

Your failure to submit a petition for hearing within 21 days from receipt of this order will constitute a waiver of your right to an administrative hearing, and this order shall become a "final order".

Should this Order become a Final Order, a party who is adversely affected by it is entitled to judicial review pursuant to section 120.68, Florida Statutes. Review proceedings are governed by the Florida Rules of Appellate Procedure. Such proceedings may be commenced by filing one copy of a Notice of Appeal with the Agency Clerk of the Department of Health and a second copy accompanied by the filing fees required by law with the Court of Appeal in the appropriate District Court. The notice must be filed within 30 days of the rendition of the final order.

From the Earth...for the Earth®



TOTAL SYSTEM SOLUTION®

REDUCES FOG & TOXIC ODOR

NET CONTENTS 64 OUNCES (1.8927 LITERS)

REVOLUTIONARY | ORGANIC | NON TOXIC | COST EFFECTIVE

www.GreenovativeTechnologies.com

From the Earth...for the Earth®

DIRECTIONS FOR USE Recommended Dosage: SYSTEMS THAT DISCHARGE TO PUBLIC SEWER

Internal Grease Traps (up to 50gal)	16oz daily
Internal Grease Traps (75-150gal)	32-48oz daily
External Grease Interceptors (750 - 3,000gal).....	88oz daily

ACTIVE INGREDIENTS:

Peat Humic Substance	12%
• 9% Humic Acid	
• 3% Other Humic Substances	

SYSTEMS CONNECTED TO SEPTIC SYSTEM

50 gallons or less internal grease trap with at least 500 gallons of additional system liquid capacity	16oz daily
75 to 51 gallons internal grease trap with at least 1,000 gallons of additional system liquid capacity	32oz daily
76 to 150 gallons internal grease trap with at least 1,400 gallons of additional system liquid capacity	48oz daily
When combined grease trap & septic tank liquid capacity is less than 2,500 gallons	44oz
When combined grease trap & septic tank liquid capacity is 2,500 gallons or more	88oz

Dosages Vary By Tank Volume, Consult Local Representative

For use in grease removal systems. • Best used within 1 year. • **Invert and shake well before use.**

Pour recommended dosage daily via a convenient drain closest to the grease trap.

WARNING: AVOID FREEZING, STORE AT ROOM TEMPERATURE (90°F OR BELOW), KEEP AWAY FROM CHILDREN, WASH SURFACES IMMEDIATELY AS PRODUCT MAY STAIN

CAUTION: Do not ingest. May cause irritation to nose, throat, and skin. If product comes in contact with skin or clothes, wash thoroughly with soap and water. In case of eye contact, wash eyes thoroughly with clean water for 15 minutes. If swallowed, induce vomiting. Immediately seek medical attention.

The manufacturer's liability is limited to the replacement of this product or refund of the purchase price.



A Division of JSH international™



MANUFACTURED BY:
GREENOVATIVE TECHNOLOGIES® MADE IN THE USA

303 Birchfield Drive | Mount Laurel, NJ 08052 | 856.234.4540 | FAX: 856.234.4921