DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

BOARD DOH FINAL MOTION VOTE ACTION

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	Α	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	Р	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

		•						
2938	Scott Vaughn for	Miami-	454.1.3.1.1 FBC: Pool wet					
Rehear		Dade	decks shall be constructed of					
	Brickell Heights Men's Spa		concrete or other nonabsorbent					
	850 S Miami Ave.		material having a smooth slip-					
	Miami, FL 33131		resistant finish. Wet deck area					
			finishes shall be designed for					
			such use and shall be installed					
			in accordance with the					
			manufacturer's specifications.					
			•					
			454.1.3.1.2 FBC: Pool wet					
			decks shall be uniformly sloped					
			at a minimum of 2 percent to a					
			maximum of 4 percent away					
			from the pool or to deck drains					
			to prevent standing water.					
			Textured deck finishes that					
			provide pitting and crevices of					
			more than 3/16 inch (4.8 mm)					
			deep that accumulate soil are					
			prohibited.					
			1					
			454.1.6.1.3 FBC: Sanitary					
			facility floors. Floors of					
			sanitary facilities shall be					
			constructed of concrete or other					
			nonabsorbent materials, shall					
			have a smooth, slip-resistant					
			finish, and shall slope to floor					
			drains. Carpets, duckboards					
			and footbaths are prohibited.					
			The intersection between the					
			floor and walls shall be coved					
			where either floor or wall is not					
			made of waterproof materials					
			such as tile or vinyl.					

Present __JK __CW __MK __AP __JL

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	T	Α	D	Y	N	Α	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	P	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2939	Scott Vaughn for	Miami-	454.1.3.1.1 FBC: Pool wet					
Rehear		Dade	decks shall be constructed of					
	Brickell Heights Women's		concrete or other nonabsorbent					
	Spa		material having a smooth slip-					
	850 S Miami Ave.		resistant finish. Wet deck area					
	Miami, FL 33131		finishes shall be designed for					
			such use and shall be installed					
			in accordance with the					
			manufacturer's specifications.					
			•					
			454.1.3.1.2 FBC: Pool wet					
			decks shall be uniformly sloped					
			at a minimum of 2 percent to a					
			maximum of 4 percent away					
			from the pool or to deck drains					
			to prevent standing water.					
			Textured deck finishes that					
			provide pitting and crevices of					
			more than 3/16 inch (4.8 mm)					
			deep that accumulate soil are					
			prohibited.					
			454.1.6.1.3 FBC: Sanitary					
			facility floors. Floors of					
			sanitary facilities shall be					
			constructed of concrete or other					
			nonabsorbent materials, shall					
			have a smooth, slip-resistant					
			finish, and shall slope to floor					
			drains. Carpets, duckboards					
			and footbaths are prohibited.					
			The intersection between the					
			floor and walls shall be coved					
			where either floor or wall is not					
			made of waterproof materials					
			such as tile or vinyl.					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	Α	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	Ρ	E	E	0	Ρ	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2942 Rehear	Aquatic Design and Engineering for BLVD US 41 at 5 th St. Sarasota, FL	Sarasota	454.1.6.5.10 FBC: Main drain outlets. All pools shall be provided with an outlet at the deepest point.						
2946	Nikki Barney for Oasis Club House 171 Northeast 30 Road Homestead, Florida 33030	Miami- Dade	454.1.2.1 FBC: Pools shall be constructed of concrete or other impervious and structurally rigid material.						
2947	Nikki Barney for Fish Hawk IWF 6015 Fishhawk crossing Blvd. Lithia FL 33547	Hillsboro ugh	454.1.2.1 FBC: Pools shall be constructed of concrete or other impervious and structurally rigid material.						
2948	Nikki Barney for Embassy Suites Hotel 300 A1A Beach Blvd St Augustine Beach, Florida 32080	St. Johns	454.1.2.1 FBC: Pools shall be constructed of concrete or other impervious and structurally rigid material.						
2949	Nikki Barney for Monterra CDD 8451 Monterra Boulevard Cooper City, Florida 33024	Broward	454.1.2.1 FBC: Pools shall be constructed of concrete or other impervious and structurally rigid material.						
2950	Altis Boca Raton (Fairway Commons 5500 North Military Trail Boca Raton, Florida 33469	Palm Beach	454.1.6.1 Sanitary facilities. Urinal requirement						

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	Р	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2951	John Gay For Apalachee Point Villas 105 Southwood Plantation Road Tallahassee, Florida 32311	Leon	454.1.2.5.5 FBC: Vacuum fittings shall be mounted no more than 15 inches (381 mm) below the water level, flush with the pool walls, and shall be provided with a springloaded safety cover which shall be in place at all times when the pool is not being vacuumed.					
2952	Gable Gates Tower LLC 2101 Southwest 62ns Avenue Miami, Florida 33155	Miami- Dade	454.1.2.5.5 FBC: Handrails shall be provided for all stairs, shall be anchored in the bottom step and the deck. 454.1.3.1.2 FBC: Pool wet decks shall be uniformly sloped at a minimum of 2 percent to a maximum of 4 percent away from the pool or to deck drains to prevent standing water.					
2953	Scott Vaughn for Brickell Heights Equinox Pool 850 S Miami Ave. Miami, FL 33131	Miami- Dade	454.1.6.1 Sanitary facilities. Urinal requirement					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	P	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2954	Icon Las Olas 500 East Las Olas Boulevard Fort Lauderdale, Florida 33301	Broward	454.1.8.4 FBC: Step treads shall have a minimum width of 10 inches (254 mm) for a minimum continuous tread length of 12 inches (305 mm).					
2955	Home 2 Suites 161 Southwest 19 th Court Dania Beach, Florida 33004	Broward	454.1.2.2.2 FBC: pool coping shall not overhang into the pool more than 11/2 inches (38 mm).by the facilities.					
2956	Blue Lagoon Condo Pool 5077 Northwest 7 th Street Miami, Florida 33126	Miami- Dade	454.1.2.3.2 FBC: Any design or logo on the pool floor or walls shall be such that it will not hinder the detection of a human in distress, algae, sediment, or other objects in the pool.					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

				. 11	OII.	OIN	. V O .	ظا	ACI	TOI			
AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	а	P	Ε	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2957	Arborwood Reserve 11730 Arborwood Preserve Fort Myers, Florida	Lee	454.1.2.6 FBC: Underwater seat benches may be installed in areas less than 5 feet (1524 mm) deep. Bench seats must be 14 to					
			18 inches (356 to 457 mm) wide 454.1.2.3.3 FBC: Pools that are not intended to be utilized for officially sanctioned					
			competition may install lap lane markings provided they meet the following criteria: the markings must be 2 to 6 inches (51 to 152 mm) wide, they					
			must terminate 5 feet (1524 mm) from the end wall in a "T" with the "T" bar at least 18 inches (1524 mm) long,					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	Α	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	а	P	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2958	'O' Residence Pool 9821-9841 East Bay Harbor Drive Bay Harbor Island, FL	Miami- Dade	454.1.2.2.2 FBC: Where interior steps protrude into the pool resulting in less than 15 feet (4572 mm) of clearance from any wall, such protrusion shall not exceed 6 feet (1828 mm) on any perpendicular line from a tangent to any pool wall from which the steps emanate. 454.1.3.1.2 FBC: Pool wet decks shall be uniformly sloped at a minimum of 2 percent to a maximum of 4 percent away from the pool or to deck drains to prevent standing water.					
2959	'O' Residence Spa 9821-9841 East Bay Harbor Drive Bay Harbor Island, FL	Miami- Dade	454.1.6.5.3.1.1 FBC: Either recessed-type or open-type gutters shall be used. Special designs can be approved provided they are within limits of sound engineering practice.					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	Р	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

	T	1	T	1		1	_	-	T	1
2960	John Wahler for	Miami-	454.1.6.5.17 FBC: Water							
		Dade	features such as waterfalls or							
	Biscayne Beach Condo		fountains in pools may use up							
	Level 6 Pool		to 20 percent of the return							
	711 Northeast 29th Street		water from the filter system,							
	Miami, Florida 33137		however all waters used in the							
			feature shall not be counted							
			toward attaining the designed							
			turnover rate.							
			454.1.6.5.3 FBC: The design							
			pattern of recirculation flow							
			shall be 100 percent through							
			the main drain piping and 100							
			percent through the perimeter							
			overflow system or 60 percent							
			through the skimmer system.							
2960a	John Wahler for	Miami-	454.1.6.1.3 FBC: Floors of							
		Dade	sanitary facilities shall be							
	Biscayne Beach Condo		constructed of concrete or other							
	Level 6 Spa Pool		nonabsorbent materials, shall							
	711 Northeast 29th Street		have a smooth, slip-resistant							
	Miami, Florida 33137		finish, and shall slope to floor							
			drains							
			454.1.3.1.7 FBC: Food or drink							
			service facilities shall not be							
			located within 12 feet (3658							
			mm) of the water's edge.							
2961	YMCA Aquatics Center	Orange	454.1.2.6 FBC: Obstructions.							
	8422 International Drive		The pool water area shall be							
	Orlando, Florida 32819		unobstructed by any type							
			structure unless justified by							
			engineering design as a part of							
			the recirculation system.							

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	Α	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	а	P	Ε	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2962	City of Key West Cozumel Park 1209 19 th Terrace Key West, Florida 33040	Monroe	454.1.6.1 Sanitary facilities. Urinal requirement					
2963	Village Pools for Waterleigh Pool 16150 Pebble Bluff Road Winter Garden, Florida 34787	Orange	454.1.2.5.3 FBC Stairs shall have a minimum tread width of 10 inches (254 mm) and a maximum width of 48 inches (1219 mm) for a minimum tread length of 24 inches (610 mm) and a maximum riser height of 10 inches (254 mm). (Sun shelf)					
2964	GB Collins for Skyview Elevated Swimming Pool 400 Cleveland Clearwater, Florida 33756	Pinellas	454.1.3.1.6 FBC: Twenty percent of the deck along the pool perimeter may be obstructed as long as any one obstruction does not exceed ten percent or ten feet (3048 mm), whichever is less, in any one area.					
2965	Village Pools for The Standard Pool 324 Center Lake Lane Oviedo, Florida 32765	Seminole	454.1.2.1 FBC: (a) Floors and walls shall be white or pastel in color and shall have the characteristics of reflecting rather than absorbing light.					
2966	Village Pools for The Standard at Gainesville Level 10 Pool 1310 West University Ave Gainesville, Florida 32601	Alachua	454.1.2.6 FBC: Benches shall not protrude into the 15-foot (4572 mm) clearance requirement of Section 454.1.2.6.					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	Α	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	а	P	Ε	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

207	II:	0	454 1 2 1 EDC - C	I					
2967	Universal City Development	Orange	454.1.2.1 FBC Gutter type pools may substitute 2-inch (51						
2968	Bevelopment		mm) tile, each a minimum size						
	Pool A 2967		of 1 inch (25 mm) on all sides,						
2969			along the pool wall edge of the						
	Pool B 2968		gutter lip.						
2970	D 1 C 20 CO								
2971	Pool C 2969								
29/1	Pool D 2970								
2972									
	Pool E 2971								
2973	D 1505								
2974	Pool F 2972								
2974	Pool G 2973								
2975	1001 0 2773								
	Pool H 2974								
2976									
2077	Pool J 2975								
2977	Pool M 2976								
2978	1 001 111 2570								
	Pool N 2977								
2979									
	Pool R 2978								
	Pool S 2979								
	1 001 3 29/9								
	6965 Turkey lake Road								
	Orlando, Florida 32819								

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	Α	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	a	Ρ	E	E	0	Ρ	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2980	The Baptist College of	Jackson	454.1.6.5.8 FBC: Main drain					
	Florida		systems and surface overflow					
	2650 Lakeshore Drive		systems which discharge to					
	Marianna, Florida 32446		collector tanks shall be sized					
	·		with a maximum flow velocity					
			of 3 feet per second (914					
			mm/s). (Gutter)					
			initial sys. (Guerra)					
			454.1.6.5.8 FBC: Main drain					
			systems and surface overflow					
			systems which discharge to					
			collector tanks shall be sized					
			with a maximum flow velocity					
			of 3 feet per second (914					
			mm/s). (Main Drain)					
			min/s). (Main Diani)					
			454.1.6.5.9.4 FBC Pools					
			greater than 30 feet (9144 mm)					
			in width shall have either floor					
			inlets only, or a combination of floor inlets and wall inlets.					
			Pools with floor inlets only					
			shall have a number of floor					
			inlets provided such that the					
			spacing between adjacent inlets					
			does not exceed 20 feet (6096					
			mm) and the spacing between					
			inlets and an adjacent wall does					
			not exceed 10 feet (3048 mm).					
		1						
2981	The Pavilion	Alachua	454.1.2.3.2 FBC: Any design					
	1000 Southwest 62 Blvd		or logo on the pool floor or					
	Gainesville, Florida 32607		walls shall be such that it will					
			not hinder the detection of a					
			human in distress, algae,					
		1	sediment, or other objects in					
			the pool.					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME	COUNTY	SECTION OF LAW OR	Т	А	D	Y	N	А	D	PROVISOS	PROVISOS	DATE
	AND ADDRESS	OF	RULE	а	P	E	E	0	P	E	RECOMMENDED	REQUIRED	LETTER
		PROJECT	AND SPECIFIC	b	R	N	S		R	N	BY BOARD	BY DOH	MAILED
			VARIANCE(S) REQUESTED	1	V	Y			V	Y			
				е									

2982	GB Collins for Lindo B&B 6359 Southwest CR 307 Trenton, Florida 32693	Gilchrest	Private Pool Conversion to Public pool serving a Bed and Breakfast. Applicant did not state specific items.					
2983 2984 2985 2986	Float Florida (4 Pods) 534 North Main Street Gainesville, Florida 32601	Alachua	Float Pod Variance Requests (4)					

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

	1		•			OIN					1	
AP #	APPLICANT'S NAME AND ADDRESS	COUNTY OF PROJECT	SECTION OF LAW OR RULE AND SPECIFIC VARIANCE(S) REQUESTED	T a b l e	A P R V	D E N Y	Y E S	N O	D E N Y	RECOMMENDED BY BOARD	PROVISOS REQUIRED BY DOH	DATE LETTER MAILED
			I			1				T		T

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME AND ADDRESS	COUNTY OF PROJECT	SECTION OF LAW OR RULE AND SPECIFIC VARIANCE(S) REQUESTED	T a b l	A P R V	D E N Y	Y E S	N O	A P R V	D E N Y	RECOMMENDED	PROVISOS REQUIRED BY DOH	DATE LETTER MAILED
				е									

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME AND ADDRESS	COUNTY OF PROJECT	SECTION OF LAW OR RULE AND SPECIFIC VARIANCE(S) REQUESTED	T a b l	A P R V	D E N Y	Y E S	N O	A P R V	D E N Y	RECOMMENDED	PROVISOS REQUIRED BY DOH	DATE LETTER MAILED
				е									

DATE: October 4, 2017 MEETING LOCATION: Orlando, RCID

RECOMMENDATIONS

AP #	APPLICANT'S NAME AND ADDRESS	COUNTY OF PROJECT	SECTION OF LAW OR RULE AND SPECIFIC VARIANCE(S) REQUESTED	T a b l	A P R V	D E N Y	Y E S	N O	A P R V	D E N Y	RECOMMENDED	PROVISOS REQUIRED BY DOH	DATE LETTER MAILED
				е									